



## 4-Port USB Charging Station

**Four USB-A Ports, up to 5 V / 2.4 A per Port, 34 W Total Output, Black**

Part No.: [102261](#)

EAN-13: 0766623102261 | UPC: 766623102261

### 4-Port USB Charging Station — Keep your portable devices fully powered and secure.

Portable USB electronics place heavy demands on their batteries for power and the Manhattan 4-Port USB Charging Station helps keep your tablets, mobile phones, digital cameras and other devices charged and ready to go. This charging station plugs into any standard wall outlet and offers rapid charging. With 34 W total power output, the station offers Smart IC technology to optimize device charging. Each port supports up to 5 V / 2.4 A to fast charge smartphones and other handheld devices. Plus, it smartly protects itself and your devices from short-circuiting, overvoltage, overcurrent and overheating.

The Manhattan 4-Port USB Charging Station is a great way to charge the devices you use most, whether at home, school or the office. It features four wide bays for securing most devices — with cases — while charging, keeping your countertop clean and clutter-free.

#### Features:

- Four USB charging ports for tablets, smartphones and other portable devices
- Each port supports up to 5 V / 2.4 A
- Smart IC for ideal power allocation
- LED status indicator

For more information on Manhattan products, consult your local dealer or visit [www.manhattan-products.com](http://www.manhattan-products.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Overload, overcurrent and overheating protection
- Sturdy, compact and heavy-duty; perfect for desktop charging for home, office, etc.
- Three-year warranty

## **Specifications:**

### Standards and Certifications

- CE
- FCC
- RoHS
- WEEE
- ETL

### Ports

- Four USB-A charging ports

### Output Characteristics

- USB-A outputs: 5 V; maximum 2.4 A; 34 W

### Input Characteristics

- AC rated voltage: 100 – 240 V
- Frequency range: 50 – 60 Hz ( $\pm 1$  Hz)
- Current:  $\leq 1$  A at 100 VAC 60 HZ

### Output Characteristics

- Rated voltage: 5 V
- Current: 2.4 A maximum (at constant voltage mode)
- Rated power: 34 watts maximum
- Overshoot voltage:  $\leq 5\%$

### Protection Characteristics

- Short-circuit (SCP) with auto-recovery mode
- Overvoltage (OVP) with auto-recovery mode
- Overcurrent (OCP) — current limit: 150% (max)
- Over-temperature (OTP)

### Physical

- Dimensions: 15.5 x 12.5 x 7.62 cm (6.1 x 4.92 x 3 in.)
- Bay width: 27 mm (1.06 in.) each
- Weight: 0.42 kg (0.94 lbs oz.)
- Housing: plastic

### Operating Environment

- Operation Temperature: 0 – 30°C (32 – 86°F)
- Storage Temperature: -20 – 65°C (-4 – 149°F)
- Humidity (noncondensing): 10 – 90%

## Package Contents

- 4-Port USB Charging Station
- 1 m (3.3 ft.) Power cord
- Instructions

